


## Basic Switch

## D3C

### Subminiature Basic Switch

- Built-in slide mechanism selects shorting or non-shorting switch timing
- 3 mm (0.12 in) long stroke
- PCB mount switch with 100 milliamp capacity
- Ideal for household appliances, sound equipment, office equipment, communications equipment, etc.
- Compact size




### Ordering Information



Actuator	Part Number			
	General Purpose		Low Operating Force	
Hinge lever	Non-shorting Model	Shorting Model	Non-shorting Model	Shorting Model
	<b>D3C-1210</b>	<b>D3C-2210</b>	<b>D3C-1220</b>	<b>D3C-2220</b>

### CONTACT FORM



### Characteristics

Electrical rating	0.1 A, 30 VDC (resistive load)	
Operating speed	1 to 500 mm/second (0.04 to 19.7 in/second)	
Operating frequency	Mechanical	200 operations per minute
	Electrical	30 operations per minute
Contact resistance	50 mΩ max.	
Insulation resistance	100 MΩ min. at 250 VDC	
Dielectric strength	250 VAC, 50/60 Hz for 1 minute between contacts of same polarity 250 VAC, 50/60 Hz for 1 minute between each terminal and ground	
Vibration	Malfunction durability	10 to 55 Hz, 1.5 mm double amplitude
Shock	Malfunction durability	300 m/s <sup>2</sup> minimum (approx. 30 g minimum)
Ambient temperature	Operating	-20° to 80°C with no icing
Humidity	Operating	65% max. at 5° to 35°C
Service life	50,000 operations minimum at the rated switch frequency	
Weight	Approx. 0.3 g	

Note: Data shown are of initial value.

SWITCHING TIMING



Non-shorting Model



Dimensions

Unit: mm (inch)


D3C



Operating characteristics	Non-shorting Model		Shorting Model	
	D3C-1210	D3C-1220	D3C-2210	D3C-2220
OF max.	130 g	40 g	130 g	40 g
RF min.	10 g	3 g	10 g	3 g
OP1	3.5 ± 0.3 mm (0.14 ± 0.01 in)		3.4 ± 0.3 mm (0.13 ± 0.01 in)	
OP2	2.5 ± 0.3 mm (0.10 ± 0.01 in)		2.6 ± 0.3 mm (0.10 ± 0.01 in)	
TTP	1.3 ± 0.4 mm (0.05 ± 0.02 in)		1.3 ± 0.4 mm (0.05 ± 0.02 in)	
FP max.	4.8 mm (0.19 inches)		4.8 mm (0.19 inches)	

Mounting holes

When mounting the D3C with screws, use M1.6 mounting screws with plain washers or spring washers. Tighten the screws to a torque of 4.9 to 9.8 X 10<sup>2</sup> N.




Note: Unless otherwise specified, a tolerance of ± 0.2 mm applies to all dimensions.

## Precautions

### ■ MOUNTING

Refer to the following dimensions for PCB mounting. The distance between two adjacent terminals is 2.54 mm.



When soldering each terminal of the D3C, apply a soldering iron rated at 30 W for no longer than three seconds. Do not impose any external force to the terminals for approximately one minute after the terminals are soldered.

Make sure that the terminals of the D3C are insulated from one another and the ground.

Do not allow the lever to be pressed beyond the TTP.

# OMRON

Omron Europe B.V. EMA-ISD, tel:+31 23 5681390, fax:+31 23 5681397, <http://www.eu.omron.com/ema>